



PROUD TO PRESENT

Present for

STYRE HMI (Human Monitoring Interface)

By OTKA TEKNO ADITAMA



Our Product



- ✓ New era monitoring equipment
- ✓ Interactive and graphical information display
- ✓ Intelligence visualization
- ✓ High resolution, high brightness, full view

- ✓ Edge calculation
- ✓ Realtime, manageable, history and summary information
- ✓ Optimum efficiency
- ✓ Alarm support



now & tomorrow partner



otka.co.id



@otkatech



@otkatechnology



@otkatechnology



@otkatechnology

Information

SPEIFICATION	VALUE			
Display	Up to 10.1" TFT LCD			
LCD viewing (T/B/L/R)	50°/70°/70°/70°		85°/85°/85°/85°	60°/60°/70°/70°
Resolution(WxH)	Up to 1024x60			
Colors	24 Bit			
Brightness	360 cd/m ²		450 cd/m ²	400 cd/m ²
Backlight	LED			
LCD life	50000 Hours			
Touch Panel	4 wires resistive touch screen (Surface hardness 4H)			
CPU	600MHz ARM Cortex-A8			
Memory	128M Flash+ 128M DDR3			
RTC	Built in			
Ethernet	NA	10M/100M adaptive	NA	110M/100M adaptive
SD Card	NA	Support	NA	Support
USB Port	USB Slave 2.0*1; USB Host 2.0*1			
Download Project	USB slave / U disk	USB slave / U disk/ Ethernet	USB slave / U disk	USB slave / U disk/ Ethernet
COM Port	COM1: RS232/RS485/RS422 COM3: RS232	COM1: RS232/RS485/RS422 COM2: RS485 COM3: RS232	COM1: RS232/RS485/RS422 COM3: RS232	COM1: RS232/RS485/RS422 COM2: RS485 COM3: RS232
Power Consumption	< 10W			
Input Power	DC24V, working range DC 9V~28V			
Power Protection	Protect from thunder strike and surging			
Power Down Allowed	< 5mS			
CE&RoHS	Complied with EN61000-6-2:2005, EN61000-6-4:2007, CE RoHS, Surge Immunity:±1KV, EFT:±2KV; ESD:4KV, Air:8KV			
Operating Temperature	0~50°C			
Storage Temperature	-20~60°C			
Operating Humidity	10~90%RH (No Condensate)			
Vibration Endurance	10~25Hz (X, Y, Z direction 2G/30 minutes)			
Cooling	Natural air cooling			
Degree of Protection	Front IP65(with NEMA panel), Back IP20			
Enclosure	ABS+PC			
Panel Cutout	192mmx138mm		260mmx202mm	
Dimension	204mmx145mmx33.8mm		273mmx213mmx36mm	
Weight	About 550g		About 850g	

Note : Specification are subject to change without notice



now & tomorrow partner



otka.co.id



@otkatech



@otkatechnology



@otkatechnology



@otkatechnology

DISCUSSION



now & tomorrow partner



otka.co.id



[@otkatech](https://www.facebook.com/otkatech)



[@otkatechnology](https://www.instagram.com/otkatechnology)



[@otkatechnology](https://twitter.com/otkatechnology)



[@otkatechnology](https://www.youtube.com/otkatechnology)



now & tomorrow partner

THANK YOU

PT. OTKA TEKNO ADITAMA

Setiabudi 2 Building 2nd floor Suite 207 B-C. Jl. H. R. Rasuna Said Kav. 62.

Jakarta 12920 ~ Indonesia

T: 021-52900828 - F: 021-52971875

Website: <http://www.otka.co.id> - Email: info@otka.co.id