



PROUD TO PRESENT



STYRE Outdoor Cabinet

By OTKA TEKNO ADITAMA

Our Product



Strong and stable framework of cabinet, which has the mounting holes.

The side panel and rear panel are the double-panel designed, the panels are fixed by the bolt from the inner.

The roof panel has the awning all around stretches out to keep from the rain, the bottom of awning have holes to keep the integrity well ventilated, which guarantees the air exchange.



Information

Name	Outdoor Cabinet Air Conditioner		
Model	OTA-STY-OCAC-A015		OTA-STY-OCAC-A3000
Air Conditioner			
Power Supply	-48VDC		AC220V/50Hz
Cooling Capacity	1500W@L35/L35	950W@L35/L35	3000W@L35/L35
Power Consumption	420W@L35/L35	580W@L35/L35	1140W@L35/L35
Internal Airflow	400m³/h		
Working Temperature Range	-40 °C ~ + 55 °C		-20 °C ~ 55 °C
Refrigerant	R134A		R410A
Cabinet			
Mounting Method	Semi-embedded Mounting		
Max Noise Level	65dB(A)		
IP Grade	IP55		IPX5
Net Weight	28 kg		50 kg
Loading Capacity	1500 kg (static loading)		
Dimensions			
Height	Up to 42 U		
Width	Up to 800 mm		
Depth	Up to 1200 mm		
Standard			
Standard	Comply with IEC60950-1 IEC60529 and GB4208-93 standard		
Standard Accessories	1*metal front with three points bolted lock; 1*metal rear door with three points bolted lock; 4* hooks on the top; 4*fans with power line; 25* cage nuts		



now & tomorrow partner



otka.co.id



@otkatech



@otkatechnology



@otkatechnology



@otkatechnology

Note : Specification are subject to change without notice

DISCUSSION





now & tomorrow partner

THANK YOU

PT. OTKA TEKNO ADITAMA

Setiabudi 2 Building 2nd floor Suite 207 B-C. Jl. H. R. Rasuna Said Kav. 62.

Jakarta 12920 ~ Indonesia

T: 021-52900828 - F: 021-52971875

Website: <http://www.otka.co.id> - Email: info@otka.co.id